

IN THE CLAIMS

1. (currently amended) A cover connectable to an electrical component to assist a tool in assembling the electrical component to another structure, the cover comprising:

a stamped metallic body section having a top surface and a component retention member, said top surface configured to form a vacuum seal with a tool; ~~and~~

~~a component retention member integrally formed with,~~ said component retention member extending from an end of said body section for releasably securing said body section to an electrical component.

2. (original) The cover of claim 1, wherein said component retention member includes a release arm normally biased toward an electrical component and deflectable in an opposite second direction away from an electrical component.

3. (original) The cover of claim 1, wherein said component retention member includes a catch surface configured to be secured to a bottom of an electric component to retain said body section on an electric component.

4. (original) The cover of claim 1, wherein said component retention member includes a release arm oriented at a retention angle to, and extending downward from, said top surface, said release arm being deflectable from said retention angle to release an electrical component.

5. (original) The cover of claim 1, wherein said component release member includes a release arm formed with and bent downward from said body section, said release arm having a lower ledge bent inward to hold an electrical component when said release arm is in a normally biased position.

6. (original) The cover of claim 1, wherein said component release member includes a release arm extending in a direction generally perpendicular to said body section and being

normally biased to form an angle with respect to said top surface, said angle being no greater than ninety degrees, said release arm being deflectable to form an obtuse angle with respect to said body section to release an electrical component.

7. (previously presented) The cover of claim 1, further comprising a stop beam extending from an end of said body section at an acute angle to said top surface, said stop beam being configured to engage an electrical component to hold an electrical component at a desired distance from said body section.

8. (original) The cover of claim 1, wherein said body section is injection molded with opposite ends molded integral with end walls of said component retention member, said end walls extending in a direction transverse to a plane containing said top surface, said end walls extending laterally along said opposite ends.

9. (original) The cover of claim 1, wherein said component retention member includes a release beam oriented parallel to a plane containing said body section, said release beam extending laterally along an end of said body section.

10. (cancelled)

11. (original) The cover of claim 1, wherein said top surface is rigid and planar to facilitate the formation of a vacuum seal.

12. (currently amended) An electrical component cover, comprising:

[[a]] an integrally formed body section having opposite peripheral edges, opposed end edges, and a planar top surface ~~extending therebetween, said top surface~~ configured to form a

said integrally formed body section including a flange provided along at least one of said peripheral edges of said body section, said flange being configured to prevent preventing

movement of an upper end of an electrical component relative to said body section in at least one direction parallel to said top surface; and

said integrally formed body section including a release arm integrally formed with extending from at least one of said opposed end edges ~~of said body section~~, said release arm ~~being~~ configured to releasably retain an electrical component.

13. (original) The cover of claim 12, wherein said release arm is normally biased toward an electrical component and deflectable in an opposite second direction away from an electrical component.

14. (original) The cover of claim 12, wherein said release arm includes a catch surface configured to be secured to a bottom of an electric component to retain said body section on an electric component.

15. (original) The cover of claim 12, wherein said release arm is oriented at a retention angle to, and extending downward from, said planar top surface, said release arm having a lever extending upward from said planar top surface, said release arm being deflectable from said retention angle to release an electric component.

16. (previously presented) The cover of claim 12, wherein said release arm is formed with and bent downward from said body section, said release arm having a lower ledge bent inward to hold an electric component when said release arm is in a normally biased position.

17. (original) The cover of claim 12, wherein said release arm extends in a direction generally perpendicular to said body section and is normally biased to form an angle with said planar top surface that is no more than ninety degrees, said release arm being deflectable to form

18. (original) The cover of claim 12, further comprising a stop beam extending from an end of said body section at an acute angle to said planar top surface, said stop beam being

configured to engage an electric component to hold an electric component a desired distance from said body section.

19. (original) The cover of claim 12, wherein said body section is injection molded with opposite ends molded integral with end walls of said release arm, said end walls extending in a direction transverse to a plane containing said planar top surface, said end walls extending laterally along said opposite ends.

20. (original) The cover of claim 12, wherein said release arm includes a release beam oriented parallel to a plane containing said body section, said release beam extending laterally along an end of said body section.

21. (original) The cover of claim 12, wherein said planar top surface is rigid to facilitate the formation of a vacuum seal.

22. (currently amended) An electrical component cover, comprising:

[[a]] an integrally formed body section having peripheral edges and a planar top surface extending between said peripheral edges, said top surface configured to form a vacuum seal with a tool for automatically assembling electrical components to other structures; and

said integrally formed body section including a release arm ~~integrally formed with~~
extending from at least one of said ~~at least two~~ opposed edges of said body section, said release arm ~~being~~ configured to releasably retain an electrical component and configured to engage an electric component to hold an electric component a desired distance from said body section.

23. (original) The cover of claim 22, wherein said release arm is normally biased toward
the electric component to engage the electric component.

24. (original) The cover of claim 22, wherein said release arm includes a catch surface configured to be secured to a bottom of an electric component to retain said body section on an electric component.

25. (original) The cover of claim 22, wherein said release arm is oriented at a retention angle to and extending downward from said planar top surface, said release arm having a lever extending upward from said planar top surface, said release arm being deflectable from said retention angle to release an electric component.

26. (previously presented) The cover of claim 22, wherein said release arm is formed with and bent downward from said body section, said release arm having a lower ledge bent inward to hold an electric component when said release arm is in a normally biased position.

27. (original) The cover of claim 22, wherein said release arm extends in a direction generally perpendicular to said body section and is normally biased to form an angle with said planar top surface that is no more than ninety degrees, said release arm being deflectable to form an obtuse angle with respect to said body section to release an electric component.

28. (previously presented) The cover of claim 22, a stop beam extending from an end of said body section at an acute angle to said planar top surface, said stop beam being configured to engage an electric component to hold an electric component at a desired distance from said body section.

29. (original) The cover of claim 22, wherein said body section is injection molded with opposite ends molded integral with end walls of said release arm, said end walls extending in a direction transverse to a plane containing said planar top surface, said end walls extending laterally along said opposite end.

30. (original) The cover of claim 22, wherein said release arm includes a release beam oriented parallel to a plane containing said body section, said release beam extending laterally along an end of said body section.